SPECIFICATION SHEET

DATE: JUL.01,98'
NO. : SS98070103
PAGE: 1/2

CUSTOMER NAME :
TYPE: HN-330A TYPE
MODEL NO. : HN-12-1641T
CUSTOMER PART NO.:

I. OUTTER DIMENSIONS :



SPECIFICATION SHEET

DATE: JUL.01,98
NO. : SS98070103

CUSTOMER NAME :
TYPE: HN-330A TYPE
MODEL NO. : HN-12-1641T
CUSTOMER PART NO.:

II. SPECIFICATIONS :

1. RATED VOLTAGE : DC 12
2. DC VOLTAGE OPERATING RANGE : DC 3 ~ 12V
3. TORQUE(LOAD) AT MAXIMUM EFFICIENCY : 35 g-cm
4. STALL TORQUE : 240 g-cm
5. NO LOAD SPEED: 5200 RPM
6. SPEED AT MAXIMUM EFFICIENCY(UNDER LOAD AT 35 g-cm) : 4270 RPM
7. NO LOAD CURRENT : 50 mA
8. CURRENT AT MAXIMUM EFFICIENCY(UNDER LOAD AT 35 g-cm) : 190 mA
9. SHAFT END PLAY : 0.8 M/M
10. STARTED TORQUE : 240 g-cm
11. INSULATION RESISTANCE : 10 M OHM
12. DIELECTRIC STRENGTH : 300V DC

SPECIFICATION SHEET

DATE: JUL.01,98'
NO. : SS98070103
PAGE: 1/2

CUSTOMER NAME :
TYPE: HN-330A TYPE
MODEL NO. : HN-12-1641T
CUSTOMER PART NO.:

I. OUTTER DIMENSIONS :



SPECIFICATION SHEET

DATE: JUL.01,98'
NO. : SS98070103
PAGE: 2/2

CUSTOMER NAME :
TYPE: HN-330A TYPE
MODEL NO. : HN-12-1641T
CUSTOMER PART NO.:

II. SPECIFICATIONS :

1. RATED VOLTAGE : DC 12
2. DC VOLTAGE OPERATING RANCE : DC 3 - 12V
3. TORQUE(LOAD) AT MAXIMUM EFFICIENCY : 35 g-cm
4. STALL TORQUE : 240 g-cm
5. NO LOAD SPEED: 5200 RPM
6. SPEED AT MAXIMUM EFFICIENCY(UNDER LOAD AT 35 g-cm) : 4270 RPM
7. NO LOAD CURRENT : 50 mA
8. CURRENT AT MAXIMUM EFFICIENCY(UNDER LOAD AT 35 g-cm) : 190 mA
9. SHAFT END PLAY : 0.8 M/M
10. STARTED TORQUE : 240 g-cm
11. INSULATION RESISTANCE : 10 M OHM
12. DIELECTRIC STRENGTH : 300V DC